



Changes: AD Liepaja added.

①	EVR3	FL270 GND	by NOTAM
②	EVR5	FL250 GND	by NOTAM
③	TRA2	FL250 3000 FT ALT	Ref. ENR 5.5
④	TRA4	FL140 GND	Ref. ENR 5.5
⑤	TRA7	FL130 GND	Ref. ENR 5.2
⑥	TRA16	FL130 3000 FT ALT	Ref. ENR 5.5

ATS airspace classification			
FIR	CTA Riga	TMA Riga	AOR Riga
UNL FL460 FL095 GND Riga ACC	FL460 FL095 Riga ACC	FL285 1500 FT ALT Riga APP	UNL FL460 FL095 GND Riga ACC

Area minimum altitude (AMA)

Each 1° quadrilateral contains Area minimum altitude (AMA) which represents the lowest altitude which may be used under instrument meteorological conditions (IMC). The AMA provides a minimum clearance of 1000 FT above all obstacles in the quadrilateral. It is represented in hundreds of feet above mean sea level.

Area minimum altitude (AMA)

Example: 1700 FT - 17

NOTE: All specified AMA values apply Riga FIR (EVRR).

- NOTE:**
- Altitudes and elevations are in FT
 - Distances are in NM and tracks are TRUE
 - For RNAV routes - RNAV 5
 - Holdings - ref. ENR 3.6
 - HX - No specific working hours
 - Legend see GEN 2.3 (Chart Symbols)

INTENTIONALLY LEFT BLANK